

www.pfcstore.com - 763-425-7890 / 800-328-2350



## BJM HIGH TEMP DEWATERING PUMP 316 STAINLESS JX15HSSF

Best Efficiency Point: 60 GPM @  
45 FTH

Wetted Material: 316 stainless /  
Silcar-FKM

Connection: 2" NPT Male

Horse Power: 2hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable  
Length: 33ft

Max Temp: 200°F



---

**SKU:** 200924

**Stock:** Out of stock contact us for  
lead time

**Categories:** [BJM High Temp  
Pumps](#)

**Model Number** JX15HSSF  
**Part Number** 200924

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

## PRODUCT DESCRIPTION

### BJM JXHF High Temp Pump

- Fahrenheit® High temperature, high head, corrosion-resistant, dewatering pump
  - HIGH TEMPERATURE up to 200°F (93°C)
    - High head up to 140'
  - Cast 316 stainless steel (ASTM 48), no welds
    - FKM Elastomers (EPDM or Buna optional)
- Double mechanical seal design with separate lip seal
  - Seal Minder® moisture detection system
    - Built in thermal protection
  - 316 stainless steel motor housing
    - Solids capability up to 3/8"
    - Class R motor insulation
      - Side discharge
      - 2 pole motor
      - 1 HP – 10 HP

### Estimated delivery 4 weeks

[BJM Curve](#)

[BJM Dims](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	80 lbs
<b>Dimensions</b>	22 × 22 × 30 in
<b>Best Efficiency Point</b>	<a href="#">60 GPM @ 45 FTH</a>

**www.pfcestore.com - 763-425-7890 / 800-328-2350**

**Voltage** 460

**Wetted Material** 316SS-VITON