PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

BJM HIGH TEMP DEWATERING PUMP 316 STAINLESS JX37HSSF

Best Efficiency Point: 120 GPM @ 80 FTH

Wetted Material: 316 stainless / Silcar-FKM

Connection: 2" NPT Male

Horse Power: 5hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F

SKU: 200940
Stock: Out of stock contact us for lead time
Categories: BJM High Temp Pumps

Model Number JX37HSSF
Part Number 200940

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

BJM JXHF High Temp Pump

• Fahrenheit® High temperature, high head, corrosion-resistant, dewatering pump
• HIGH TEMPERATURE up to 200°F (93°C)
• High head up to 140’
• Cast 316 stainless steel (ASTM 48), no welds
• FKM Elastomers (EPDM or Buna optional)
• Double mechanical seal design with separate lip seal
• Seal Minder® moisture detection system
• Built in thermal protection
• 316 stainless steel motor housing
• Solids capability up to 3/8”
• Class R motor insulation
• Side discharge
• 2 pole motor
• 1 HP – 10 HP

Estimated delivery 4 weeks

BJM Curve

BJM Dims

ADDITIONAL INFORMATION

Weight	120 lbs
Dimensions	22 × 22 × 30 in
Best Efficiency Point	120 GPM @ 80 FTH

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

Voltage	460
Wetted Material	316SS-VITON