

www.pfcestore.com - 763-425-7890 / 800-328-2350



BJM HIGH TEMP DEWATERING PUMP 316 STAINLESS JX55HSSF

Best Efficiency Point: 200 GPM @ 68 FTH

Wetted Material: 316 stainless / Silcar-FKM

Connection: 3" NPT Female

Horse Power: 7.5hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F



SKU: 200948

Stock: Out of stock contact us for

lead time

Categories: BJM High Temp

<u>Pumps</u>

Model Number JX55HSSF **Part Number** 200948



www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

BJM JXHF High Temp Pump

- Fahrenheit® High temperature, high head, corrosion-resistant, dewatering pump
 - HIGH TEMPERATURE up to 200°F (93°C)
 - High head up to 140'
 - Cast 316 stainless steel (ASTM 48), no welds
 - FKM Elastomers (EPDM or Buna optional)
 - Double mechanical seal design with separate lip seal
 - Seal Minder® moisture detection system
 - Built in thermal protection
 - 316 stainless steel motor housing
 - Solids capability up to 3/8"
 - Class R motor insulation
 - Side discharge
 - 2 pole motor
 - 1 HP 10 HP

Estimated delivery 4 weeks

BJM Curve

BJM Dims

ADDITIONAL INFORMATION

Weight 240 lbs

Dimensions $30 \times 30 \times 34 \text{ in}$

Best Efficiency Point 200 GPM @ 68 FTH



Voltage <u>460</u>

www.pfcestore.com - 763-425-7890 / 800-328-2350

Wetted Material 316SS-VITON