

www.pfcestore.com - 763-425-7890 / 800-328-2350



BJM HIGH TEMP DEWATERING PUMP 316 STAINLESS JX75HSSF

Best Efficiency Point: 350 GPM @
70 FTH

Wetted Material: 316 stainless /
Silcar-FKM

Connection: 4" NPT Female

Horse Power: 10hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable
Length: 33ft

Max Temp: 200°F



SKU: 200954

Stock: Out of stock contact us for
lead time

Categories: [BJM High Temp
Pumps](#)

Model Number JX75HSSF
Part Number 200954

www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

BJM JXHF High Temp Pump

- Fahrenheit® High temperature, high head, corrosion-resistant, dewatering pump
 - HIGH TEMPERATURE up to 200°F (93°C)
 - High head up to 140'
 - Cast 316 stainless steel (ASTM 48), no welds
 - FKM Elastomers (EPDM or Buna optional)
- Double mechanical seal design with separate lip seal
 - Seal Minder® moisture detection system
 - Built in thermal protection
 - 316 stainless steel motor housing
 - Solids capability up to 3/8"
 - Class R motor insulation
 - Side discharge
 - 2 pole motor
 - 1 HP – 10 HP

Estimated delivery 4 weeks

[BJM Curve](#)

[BJM Dims](#)

ADDITIONAL INFORMATION

Weight	240 lbs
Dimensions	30 × 30 × 34 in
Best Efficiency Point	350 GPM @ 70 FTH

www.pfcestore.com - 763-425-7890 / 800-328-2350

Voltage	<u>460</u>
Wetted Material	<u>316SS-VITON</u>