

www.pfcestore.com - 763-425-7890 / 800-328-2350



BJM HIGH TEMP SHREDDER PUMP 316 STAINLESS SKX08CSSF

Best Efficiency Point: 55 GPM @ 32 FTH

Wetted Material: 316 stainless / Silcar-FKM

Connection: 2" NPT Male

Horse Power: 1hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F



SKU: 200800 Stock: Out of stock contact us for lead time Categories: <u>BJM High Temp</u> <u>Pumps</u>

Model Number SKX08CSSF Part Number 200800

Page: 1

PFC eStore Pumps, Filters & Controls store with B2B solution



www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

BJM SKXF High Temp Pump

- Fahrenheit® High temperature, corrosion-resistant 316 stainless steel, shredding/cutting solids handling, non-clog shredder pump
- Wear-resistant shredding and cutting system designed to tear, break, rin solids

rip solids

- Tungsten carbide-tipped impeller
 - Max solids from 1.6" 3.5"
 - Dual mechanical seals
 - Built-in thermal protection
- Seal Minder® moisture detection system
 - ANSI or NPT discharge flange
 - Integrated, removable pump stand
 - 33' power and Seal Minder Cable
 - Heavy duty lifting rings
 - Class R motor insulation
 - 2 pole and 4 pole motors available
 - Single-phase and 3-phase voltages
 - 1 HP 20 HP

Estimated delivery 4 weeks

BJM Curve

BJM Dims

<u>BJM Manual</u>

ADDITIONAL INFORMATION



Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

Weight	80 lbs
Dimensions	22 × 22 × 34 in
Best Efficiency Point	<u>55 GPM @ 32 FTH</u>
Voltage	<u>460</u>
Wetted Material	316SS-VITON