# PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



## BJM HIGH TEMP SHREDDER PUMP 316 STAINLESS SKX08CSSF

Best Efficiency Point: 55 GPM @ 32 FTH

Wetted Material: 316 stainless / Silcar-FKM

Connection: 2" NPT Male

Horse Power: 1hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F



**SKU:** 200800

Stock: Out of stock contact us for

lead time

Categories: BJM High Temp

<u>Pumps</u>

**Model Number** SKX08CSSF **Part Number** 200800



www.pfcestore.com - 763-425-7890 / 800-328-2350

#### PRODUCT DESCRIPTION

BJM SKXF High Temp Pump

- Fahrenheit® High temperature, corrosion-resistant 316 stainless steel, shredding/cutting solids handling, non-clog shredder pump
- Wear-resistant shredding and cutting system designed to tear, break, rip solids
  - Tungsten carbide-tipped impeller
    - Max solids from 1.6" 3.5"
      - Dual mechanical seals
    - Built-in thermal protection
  - Seal Minder® moisture detection system
    - ANSI or NPT discharge flange
    - Integrated, removable pump stand
      - 33' power and Seal Minder Cable
        - Heavy duty lifting rings
        - Class R motor insulation
    - 2 pole and 4 pole motors available
    - Single-phase and 3-phase voltages
      - 1 HP 20 HP

## **Estimated delivery 4 weeks**

BJM Curve

BJM Dims

**BJM Manual** 

### **ADDITIONAL INFORMATION**



#### www.pfcestore.com - 763-425-7890 / 800-328-2350

Weight 80 lbs

**Dimensions**  $22 \times 22 \times 34 \text{ in}$ 

**Best Efficiency Point** 55 GPM @ 32 FTH

Voltage 460

Wetted Material 316SS-VITON