

www.pfcstore.com - 763-425-7890 / 800-328-2350



## BJM HIGH TEMP DEWATERING PUMP CAST IRON J08F-460V

Best Efficiency Point: 45 GPM @ 37  
FTH

Wetted Material: Cast Iron / Silcar-  
FKM


Connection: 2" NPT Male

Horse Power: 1hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable  
Length: 33ft

Max Temp: 200°F



---

**SKU:** 200874

**Stock:** Out of stock contact us for  
lead time

**Categories:** [BJM High Temp  
Pumps](#)

**Model Number** J08F-460

**Part Number** 200874

## PRODUCT DESCRIPTION

### BJM JF High Temp Pump

- Fahrenheit® High Temperature general sump dewatering
  - HIGH TEMPERATURE up to up to 200°F (93°C)
    - High flow up to 650 GPM
- Double mechanical seal design with separate lip seal
  - Cast iron construction
  - 304 stainless steel motor housing
    - Solids capability up to 3/8"
- Seal Minder® moisture detection system
  - Built in thermal protection
    - Class R insulation
    - Side discharge
      - 2 pole motor
      - 1 HP - 10 HP

### Estimated delivery 4 weeks

[BJM Curve](#)

[BJM Dims](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	80 lbs
<b>Dimensions</b>	20 × 20 × 26 in
<b>Best Efficiency Point</b>	<a href="#">45 GPM @ 37 FTH</a>
<b>Voltage</b>	<a href="#">460</a>

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

**Wetted Material**

CAST IRON-304SS-VITON

Best Efficiency Point: 45 GPM @ 37 FTH

Wetted Material: Cast Iron / Silcar-FKM

Connection: 2" NPT Male

Horse Power: 1hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F