# PFC estore

www.pfcestore.com - 763-425-7890 / 800-328-2350



# BJM HIGH TEMP DEWATERING PUMP CAST IRON J22F-460V

Best Efficiency Point: 120 GPM @ 53 FTH

Wetted Material: Cast Iron / Silcar-FKM

Connection: 3" NPT Male

Horse Power: 3hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F



**SKU:** 200886

Stock: Out of stock contact us for

lead time

Categories: BJM High Temp

<u>Pumps</u>

**Model Number** J22F-460 **Part Number** 200886



www.pfcestore.com - 763-425-7890 / 800-328-2350

#### PRODUCT DESCRIPTION

BJM JF High Temp Pump

- Fahrenheit® High Temperature general sump dewatering
  - HIGH TEMPERATURE up to up to 200°F (93°C)
    - High flow up to 650 GPM
  - Double mechanical seal design with separate lip seal
    - Cast iron construction
    - 304 stainless steel motor housing
      - Solids capability up to 3/8"
    - Seal Minder® moisture detection system
      - Built in thermal protection
        - Class R insulation
          - Side discharge
          - 2 pole motor
          - 1 HP 10 HP

## **Estimated delivery 4 weeks**

**BJM Curve** 

**BJM Dims** 

### **ADDITIONAL INFORMATION**

Weight 120 lbs

**Dimensions**  $20 \times 20 \times 26 \text{ in}$ 

**Best Efficiency Point** 120 GPM @ 53 FTH

Voltage 460



www.pfcestore.com - 763-425-7890 / 800-328-2350

Wetted Material CAST IRON-304SS-VITON