

www.pfcstore.com - 763-425-7890 / 800-328-2350



BJM HIGH TEMP DEWATERING PUMP CAST IRON J75F-460V

Best Efficiency Point: 400 GPM @
60 FTH

Wetted Material: Cast Iron / Silcar-
FKM


Connection: 4" NPT Female

Horse Power: 10hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable
Length: 33ft

Max Temp: 200°F



SKU: 200909

Stock: Out of stock contact us for
lead time

Categories: [BJM High Temp
Pumps](#)

Model Number J75F-460

Part Number 200909

www.pfcstore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

BJM JF High Temp Pump

- Fahrenheit® High Temperature general sump dewatering
 - HIGH TEMPERATURE up to up to 200°F (93°C)
 - High flow up to 650 GPM
- Double mechanical seal design with separate lip seal
 - Cast iron construction
 - 304 stainless steel motor housing
 - Solids capability up to 3/8"
- Seal Minder® moisture detection system
 - Built in thermal protection
 - Class R insulation
 - Side discharge
 - 2 pole motor
 - 1 HP – 10 HP

Estimated delivery 4 weeks

[BJM Curve](#)

[BJM Dims](#)

ADDITIONAL INFORMATION

Weight	300 lbs
Dimensions	28 × 30 × 36 in
Best Efficiency Point	400 GPM @ 60 FTH
Voltage	460

www.pfcstore.com - 763-425-7890 / 800-328-2350

Wetted Material

CAST IRON-304SS-VITON