

www.pfcestore.com - 763-425-7890 / 800-328-2350



BJM HIGH TEMP DEWATERING PUMP CAST IRON J75F-460V

Best Efficiency Point: 400 GPM @ 60 FTH

Wetted Material: Cast Iron / Silcar-FKM

Connection: 4" NPT Female

Horse Power: 10hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F



SKU: 200909 Stock: Out of stock contact us for lead time Categories: <u>BJM High Temp</u> <u>Pumps</u>

> Model Number J75F-460 Part Number 200909

Page: 1

PFC eStore Pumps, Filters & Controls store with B2B solution



www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

BJM JF High Temp Pump

- Fahrenheit® High Temperature general sump dewatering
 - HIGH TEMPERATURE up to up to 200°F (93°C)
 - High flow up to 650 GPM
 - Double mechanical seal design with separate lip seal
 - Cast iron construction
 - 304 stainless steel motor housing
 - Solids capability up to 3/8"
 - Seal Minder® moisture detection system
 - Built in thermal protection
 - Class R insulation
 - Side discharge
 - 2 pole motor
 - 1 HP 10 HP

Estimated delivery 4 weeks

BJM Curve

BJM Dims

ADDITIONAL INFORMATION

 Weight
 300 lbs

 Dimensions
 28 × 30 × 36 in

 Best Efficiency Point
 400 GPM @ 60 FTH

460

Voltage

Page: 2

PFC eStore Pumps, Filters & Controls store with B2B solution September 7, 2025



www.pfcestore.com - 763-425-7890 / 800-328-2350

Wetted Material CAST IRON-304SS-VITON