

www.pfcstore.com - 763-425-7890 / 800-328-2350



## BJM HIGH TEMP SHREDDER PUMP 316 STAINLESS SKX110CSSF

Best Efficiency Point: 425 GPM @  
55 FTH

Wetted Material: 316 stainless /  
Silcar-FKM


Connection: 6" ANSI Slip Weld  
Flange

Horse Power: 15hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable  
Length: 33ft

Max Temp: 200°F



---

**SKU:** 200822

**Stock:** Out of stock contact us for  
lead time

**Categories:** [BJM High Temp  
Pumps](#)

**Model Number** SKX110CSSF

www.pfcstore.com - 763-425-7890 / 800-328-2350

**Part Number 200822**

## **PRODUCT DESCRIPTION**

### **BJM SKXF High Temp Pump**

- Fahrenheit® High temperature, corrosion-resistant 316 stainless steel, shredding/cutting solids handling, non-clog shredder pump
- Wear-resistant shredding and cutting system designed to tear, break, rip solids
  - Tungsten carbide-tipped impeller
    - Max solids from 1.6" – 3.5"
    - Dual mechanical seals
    - Built-in thermal protection
  - Seal Minder® moisture detection system
    - ANSI or NPT discharge flange
  - Integrated, removable pump stand
  - 33' power and Seal Minder Cable
    - Heavy duty lifting rings
    - Class R motor insulation
  - 2 pole and 4 pole motors available
  - Single-phase and 3-phase voltages
    - 1 HP – 20 HP

**Estimated delivery 4 weeks**

[BJM Curve](#)

[BJM Dims](#)

[BJM Manual](#)

www.pfcstore.com - 763-425-7890 / 800-328-2350

ADDITIONAL INFORMATION

Weight	620 lbs
Dimensions	34 × 34 × 40 in
Best Efficiency Point	<u>425 GPM @ 55 FTH</u>
Voltage	<u>460</u>
Wetted Material	<u>316SS-VITON</u>