

www.pfcstore.com - 763-425-7890 / 800-328-2350



## BJM HIGH TEMP SHREDDER PUMP 316 STAINLESS SKX150CSSF

Best Efficiency Point: 550 GPM @  
65 FTH

Wetted Material: 316 stainless /  
Silcar-FKM

Connection: 6" ANSI Slip Weld  
Flange

Horse Power: 20hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable  
Length: 33ft

Max Temp: 200°F



---

**SKU:** 200824

**Stock:** Out of stock contact us for  
lead time

**Categories:** [BJM High Temp  
Pumps](#)

**Model Number** SKX150CSSF

www.pfcstore.com - 763-425-7890 / 800-328-2350

**Part Number 200824**

## **PRODUCT DESCRIPTION**

### **BJM SKXF High Temp Pump**

- Fahrenheit® High temperature, corrosion-resistant 316 stainless steel, shredding/cutting solids handling, non-clog shredder pump
- Wear-resistant shredding and cutting system designed to tear, break, rip solids
  - Tungsten carbide-tipped impeller
    - Max solids from 1.6" – 3.5"
    - Dual mechanical seals
    - Built-in thermal protection
  - Seal Minder® moisture detection system
    - ANSI or NPT discharge flange
  - Integrated, removable pump stand
  - 33' power and Seal Minder Cable
    - Heavy duty lifting rings
    - Class R motor insulation
  - 2 pole and 4 pole motors available
  - Single-phase and 3-phase voltages
    - 1 HP – 20 HP

**Estimated delivery 4 weeks**

[BJM Curve](#)

[BJM Dims](#)

[BJM Manual](#)

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

## ADDITIONAL INFORMATION

<b>Weight</b>	640 lbs
<b>Dimensions</b>	34 × 34 × 40 in
<b>Best Efficiency Point</b>	<u>550 GPM @ 65 FTH</u>
<b>Voltage</b>	<u>460</u>
<b>Wetted Material</b>	<u>316SS-VITON</u>