PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



BJM HIGH TEMP SHREDDER PUMP 316 STAINLESS SKX150CSSF

Best Efficiency Point: 550 GPM @ 65 FTH

Wetted Material: 316 stainless / Silcar-FKM

Connection: 6" ANSI Slip Weld Flange

Horse Power: 20hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F



SKU: 200824

Stock: Out of stock contact us for

lead time

Categories: BJM High Temp

<u>Pumps</u>

Model Number SKX150CSSF



www.pfcestore.com - 763-425-7890 / 800-328-2350

Part Number 200824

PRODUCT DESCRIPTION

BJM SKXF High Temp Pump

- Fahrenheit® High temperature, corrosion-resistant 316 stainless steel, shredding/cutting solids handling, non-clog shredder pump
- Wear-resistant shredding and cutting system designed to tear, break, rip solids
 - Tungsten carbide-tipped impeller
 - Max solids from 1.6" 3.5"
 - Dual mechanical seals
 - Built-in thermal protection
 - Seal Minder® moisture detection system
 - ANSI or NPT discharge flange
 - Integrated, removable pump stand
 - 33' power and Seal Minder Cable
 - Heavy duty lifting rings
 - Class R motor insulation
 - 2 pole and 4 pole motors available
 - Single-phase and 3-phase voltages
 - 1 HP 20 HP

Estimated delivery 4 weeks

BJM Curve

BJM Dims

BJM Manual



www.pfcestore.com - 763-425-7890 / 800-328-2350

ADDITIONAL INFORMATION

Weight 640 lbs

Dimensions $34 \times 34 \times 40 \text{ in}$

Best Efficiency Point 550 GPM @ 65 FTH

Voltage 460

Wetted Material 316SS-VITON