

#### www.pfcestore.com - 763-425-7890 / 800-328-2350



### BJM HIGH TEMP SHREDDER PUMP 316 STAINLESS SKX15CSSF

Best Efficiency Point: 125 GPM @ 32 FTH

Wetted Material: 316 stainless / Silcar-FKM

Connection: 3" NPT Male

Horse Power: 2hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F



SKU: 200804 Stock: Out of stock contact us for lead time Categories: <u>BJM High Temp</u> <u>Pumps</u>

Model Number SKX15CSSF Part Number 200804

Page: 1

PFC eStore Pumps, Filters & Controls store with B2B solution



www.pfcestore.com - 763-425-7890 / 800-328-2350

# **PRODUCT DESCRIPTION**

BJM SKXF High Temp Pump

- Fahrenheit® High temperature, corrosion-resistant 316 stainless steel, shredding/cutting solids handling, non-clog shredder pump
- Wear-resistant shredding and cutting system designed to tear, break, rin solids

rip solids

- Tungsten carbide-tipped impeller
  - Max solids from 1.6" 3.5"
    - Dual mechanical seals
  - Built-in thermal protection
- Seal Minder® moisture detection system
  - ANSI or NPT discharge flange
  - Integrated, removable pump stand
    - 33' power and Seal Minder Cable
      - Heavy duty lifting rings
      - Class R motor insulation
  - 2 pole and 4 pole motors available
  - Single-phase and 3-phase voltages
    - 1 HP 20 HP

Estimated delivery 4 weeks

BJM Curve

**BJM Dims** 

<u>BJM Manual</u>

# **ADDITIONAL INFORMATION**



**Clear Solutions Technology Company** 

#### www.pfcestore.com - 763-425-7890 / 800-328-2350

Weight	100 lbs
Dimensions	22 × 22 × 34 in
<b>Best Efficiency Point</b>	<u>125 GPM @ 32 FTH</u>
Voltage	<u>460</u>
Wetted Material	316SS-VITON