

www.pfcestore.com - 763-425-7890 / 800-328-2350



## BJM HIGH TEMP SHREDDER PUMP 316 STAINLESS SKX37CSSF

Best Efficiency Point: 200 GPM @  
45 FTH

Wetted Material: 316 stainless /  
Silcar-FKM

Connection: 4" NPT Female

Horse Power: 5hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable  
Length: 33ft

Max Temp: 200°F



---

**SKU:** 200812

**Stock:** Out of stock contact us for  
lead time

**Categories:** [BJM High Temp  
Pumps](#)

**Model Number** SKX37CSSF  
**Part Number** 200812

## PRODUCT DESCRIPTION

### BJM SKXF High Temp Pump

- Fahrenheit® High temperature, corrosion-resistant 316 stainless steel, shredding/cutting solids handling, non-clog shredder pump
- Wear-resistant shredding and cutting system designed to tear, break, rip solids
  - Tungsten carbide-tipped impeller
    - Max solids from 1.6" – 3.5"
    - Dual mechanical seals
    - Built-in thermal protection
- Seal Minder® moisture detection system
  - ANSI or NPT discharge flange
- Integrated, removable pump stand
  - 33' power and Seal Minder Cable
    - Heavy duty lifting rings
    - Class R motor insulation
- 2 pole and 4 pole motors available
- Single-phase and 3-phase voltages
  - 1 HP – 20 HP

### Estimated delivery 4 weeks

[BJM Curve](#)

[BJM Dims](#)

[BJM Manual](#)

## ADDITIONAL INFORMATION

www.pfcestore.com - 763-425-7890 / 800-328-2350

Weight	145 lbs
Dimensions	22 × 22 × 34 in
Best Efficiency Point	<u>200 GPM @ 45 FTH</u>
Voltage	<u>460</u>
Wetted Material	<u>316SS-VITON</u>