PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



BJM HIGH TEMP SHREDDER PUMP 316 STAINLESS SKX37CSSF

Best Efficiency Point: 200 GPM @ 45 FTH

Wetted Material: 316 stainless / Silcar-FKM

Connection: 4" NPT Female

Horse Power: 5hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F



SKU: 200812

Stock: Out of stock contact us for

lead time

Categories: BJM High Temp

<u>Pumps</u>

Model Number SKX37CSSF **Part Number** 200812



www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

BJM SKXF High Temp Pump

- Fahrenheit® High temperature, corrosion-resistant 316 stainless steel, shredding/cutting solids handling, non-clog shredder pump
- Wear-resistant shredding and cutting system designed to tear, break, rip solids
 - Tungsten carbide-tipped impeller
 - Max solids from 1.6" 3.5"
 - Dual mechanical seals
 - Built-in thermal protection
 - Seal Minder® moisture detection system
 - ANSI or NPT discharge flange
 - · Integrated, removable pump stand
 - 33' power and Seal Minder Cable
 - Heavy duty lifting rings
 - Class R motor insulation
 - 2 pole and 4 pole motors available
 - Single-phase and 3-phase voltages
 - 1 HP 20 HP

Estimated delivery 4 weeks

BJM Curve

BJM Dims

BJM Manual

ADDITIONAL INFORMATION



Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

Weight 145 lbs

Dimensions $22 \times 22 \times 34 \text{ in}$

Best Efficiency Point 200 GPM @ 45 FTH

Voltage 460

Wetted Material 316SS-VITON