

www.pfcestore.com - 763-425-7890 / 800-328-2350



## BJM HIGH TEMP SHREDDER PUMP 316 STAINLESS SKX75CSSF

Best Efficiency Point: 400 GPM @  
42 FTH

Wetted Material: 316 stainless /  
Silcar-FKM

Connection: 4" NPT Female

Horse Power: 10hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable  
Length: 33ft

Max Temp: 200°F



---

**SKU:** 200819

**Stock:** Out of stock contact us for  
lead time

**Categories:** [BJM High Temp  
Pumps](#)

**Model Number** SKX75CSSF  
**Part Number** 200819

## PRODUCT DESCRIPTION

### BJM SKXF High Temp Pump

- Fahrenheit® High temperature, corrosion-resistant 316 stainless steel, shredding/cutting solids handling, non-clog shredder pump
- Wear-resistant shredding and cutting system designed to tear, break, rip solids
  - Tungsten carbide-tipped impeller
    - Max solids from 1.6" – 3.5"
    - Dual mechanical seals
    - Built-in thermal protection
- Seal Minder® moisture detection system
  - ANSI or NPT discharge flange
- Integrated, removable pump stand
- 33' power and Seal Minder Cable
  - Heavy duty lifting rings
  - Class R motor insulation
- 2 pole and 4 pole motors available
- Single-phase and 3-phase voltages
  - 1 HP – 20 HP

### Estimated delivery 4 weeks

[BJM Curve](#)

[BJM Dims](#)

[BJM Manual](#)

## ADDITIONAL INFORMATION

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

|                              |                         |
|------------------------------|-------------------------|
| <b>Weight</b>                | 420 lbs                 |
| <b>Dimensions</b>            | 34 × 34 × 40 in         |
| <b>Best Efficiency Point</b> | <u>400 GPM @ 42 FTH</u> |
| <b>Voltage</b>               | <u>460</u>              |
| <b>Wetted Material</b>       | <u>316SS-VITON</u>      |