

www.pfcestore.com - 763-425-7890 / 800-328-2350



BJM HIGH TEMP SHREDDER PUMP CAST IRON SK150C-F-460V

Best Efficiency Point: 550 GPM @ 65 FTH

Wetted Material: Cast Iron / Silcar-FKM

Connection: 6" Ansi slip welded flange

Horse Power: 20hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F



SKU: 200796 Stock: Out of stock contact us for lead time Categories: <u>BJM High Temp</u> <u>Pumps</u>

Model Number SK150C-F-460

Page: 1

PFC eStore Pumps, Filters & Controls store with B2B solution



www.pfcestore.com - 763-425-7890 / 800-328-2350

Part Number 200796

PRODUCT DESCRIPTION

BJM SK High Temp Pump

• Fahrenheit® High temperature shredder pump

- Withstands temperatures up to 200°F (93°C)
- 304 stainless steel for superior corrosion resistance
 - Wear-resistant shredding system
 - Heavy duty lifting rings
 - Built in thermal protection
 - Cable entry sealing system to prevent wicking
 - ANSI For NPT discharge flange
 - Seal Minder® moisture detection system
 - Class F motor insulation
 - Integral pump stand

Estimated delivery 4 weeks

BJM Curve

BJM Dims

BJM Manual

ADDITIONAL INFORMATION

Weight 640 lbs

Dimensions $30 \times 42 \times 44$ in

Best Efficiency Point 550 GPM @ 65 FTH

Voltage

<u>460</u>

PFC eStore

September 8, 2025

Pumps, Filters & Controls store with B2B



www.pfcestore.com - 763-425-7890 / 800-328-2350

Wetted Material

CAST IRON-304SS-VITON