

www.pfcstore.com - 763-425-7890 / 800-328-2350



BJM HIGH TEMP SHREDDER PUMP CAST IRON SK22C-F-460V

Best Efficiency Point: 165 GPM @
45 FTH

Wetted Material: Cast Iron / Silcar-
FKM

Connection: 3" NPT Male

Horse Power: 3hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable
Length: 33ft

Max Temp: 200°F



SKU: 200780

Stock: Out of stock contact us for
lead time

Categories: [BJM High Temp
Pumps](#)

Model Number SK22C-F-460

Part Number 200780

www.pfcstore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

BJM SK High Temp Pump

- Fahrenheit® High temperature shredder pump
 - Withstands temperatures up to 200°F (93°C)
- 304 stainless steel for superior corrosion resistance
 - Wear-resistant shredding system
 - Heavy duty lifting rings
 - Built in thermal protection
- Cable entry sealing system to prevent wicking
 - ANSI For NPT discharge flange
- Seal Minder® moisture detection system
 - Class F motor insulation
 - Integral pump stand

Estimated delivery 4 weeks

[BJM Curve](#)

[BJM Dims](#)

[BJM Manual](#)

ADDITIONAL INFORMATION

Weight	140 lbs
Dimensions	20 × 22 × 30 in
Best Efficiency Point	165 GPM @ 45 FTH
Voltage	460

www.pfcstore.com - 763-425-7890 / 800-328-2350

Wetted Material

CAST IRON-304SS-VITON

Best Efficiency Point: 165 GPM @ 45 FTH

Wetted Material: Cast Iron / Silcar-FKM

Connection: 3" NPT Male

Horse Power: 3hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F