

www.pfcestore.com - 763-425-7890 / 800-328-2350



BJM HIGH TEMP SHREDDER PUMP CAST IRON SK55C-F-460V

Best Efficiency Point: 350 GPM @ 35 FTH

Wetted Material: Cast Iron / Silcar-FKM

Connection: 4" NPT Female

Horse Power: 7.5hp

Voltage: 3/60/460v

Power Cord & Seal Minder cable Length: 33ft

Max Temp: 200°F



SKU: 200788 Stock: Out of stock contact us for lead time Categories: <u>BJM High Temp</u> <u>Pumps</u>

Model Number SK55C-F-460 Part Number 200788

Page: 1

PFC eStore Pumps, Filters & Controls store with B2B solution



www.pfcestore.com - 763-425-7890 / 800-328-2350

PRODUCT DESCRIPTION

BJM SK High Temp Pump

- Fahrenheit® High temperature shredder pump
- Withstands temperatures up to 200°F (93°C)
- 304 stainless steel for superior corrosion resistance
 - Wear-resistant shredding system
 - Heavy duty lifting rings
 - Built in thermal protection
 - Cable entry sealing system to prevent wicking
 - ANSI For NPT discharge flange
 - Seal Minder® moisture detection system
 - Class F motor insulation
 - Integral pump stand

Estimated delivery 4 weeks

BJM Curve

BJM Dims

<u>BJM Manual</u>

ADDITIONAL INFORMATION

| Weight | 400 lbs |
|-----------------------|-----------------|
| Dimensions | 26 × 36 × 40 in |
| Post Efficiency Doint | |

Best Efficiency Point <u>350 GPM @ 35 FTH</u>

460

Voltage



www.pfcestore.com - 763-425-7890 / 800-328-2350

Wetted Material CAST IRON-304SS-VITON