



## BJM KZE 550 SUBMERSIBLE PUMP FOR HEAVY DUTY SLURRY'S

Connections 8"ANSI | Max Temp  
104°F | Cord Length 50' | Ductile  
Iron/Hi-Chrome | 460 Volts | BEP  
1500 GPM @ 115 FTH



---

**SKU:** 203824

**Stock:** Out of stock contact us for  
lead time

**Categories:** [BJM Slurry Pumps](#)

**Model Number** KZE550-460 VOLT  
**Part Number** 203824

## PRODUCT DESCRIPTION

Max Submersion Depth 65' or Length of cord

Dual Mechanical Seals

Ductile Iron & Hi Chrome

Buna Lip Seals & O-rings

www.pfcstore.com - 763-425-7890 / 800-328-2350

Power Cord 50' SOOW

Max Temp 104°F

Yes Seal Minder

Estimated delivery 3 weeks

Product photo could vary from the actual product

### **PUMP FEATURES:**

- Sealing system – oil-cooled and lubricated double mechanical seal design with SiC vs. SiC faces and Buna N elastomers. Seal chamber protected from pumpage by labyrinth rings and lipseal. Seal Minder® leak detection probe.
- Bearing system – permanently lubricated upper and lower bearings with high temperature grease to extend life. Upper radial bearing is roller bearing design. Lower radial and axial thrust bearing is double row angular contact design.
  - Impeller – Semi-open, hard metal slurry type impeller capable of passing 1" solids to accommodate heavy slurry loading.
- Agitator – Hard metal agitator keeps heavy solids from settling and allows them to be pumped away.
- Pump materials of construction – 28% high chrome iron wear parts (volute, impeller, wear plate).
  - 403SS shaft and impeller key.
  - 304SS hardware & fasteners.
    - Cast iron motor housing.
    - High chrome iron agitator.

### **MOTOR FEATURES:**

- Power Cable – 50' length standard, GGC cable with Zener diode for use with ground check controls. Conductor size AWG #6 (50 HP) and AWG #4 (75 HP).
- Sensor Cable – 50' length for Seal Minder® moisture sensing probe and

www.pfcstore.com - 763-425-7890 / 800-328-2350

motor thermal sensors.

- Cable Entry Sealing System – compression fitting with Buna N grommet. Individually isolated and potted leads to prevent moisture intrusion and wicking.
  - Class H insulation.
  - 1.15 Service factor.
- 104° F (40° C) Max liquid temperature.
  - 4 pole motor speed.
- High-chrome agitator helps keep solids suspended in liquid and helps prevent pump from clogging.
- Specifications dependent on model and may change without notice.

[KZE Specs](#)

[KZE Dimensions](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	1955 lbs
<b>Dimensions</b>	65 × 33 × 52 in
<b>Best Efficiency Point</b>	<a href="#">1500 GPM @ 115 FTH</a>
<b>Connections</b>	<a href="#">8" ANSI FLANGE</a>
<b>Hertz</b>	<a href="#">60</a>
<b>Horse Power</b>	<a href="#">75</a>
<b>Motor Type</b>	<a href="#">Continuous Duty</a>
<b>Phase</b>	<a href="#">3</a>
<b>RPM</b>	<a href="#">1800</a>
<b>Solid Size</b>	<a href="#">1"</a>
<b>Voltage</b>	<a href="#">460</a>

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

**Wetted Material**

DUCTILE IRON/HI-CHROME/BUNA/SILCAR

Connections 8"ANSI | Max Temp 104°F | Cord Length 50' | Ductile Iron/HI-Chrome | 460 Volts | BEP 1500 GPM @ 115 FTH