



## GENERAL PUMP KE22A - 10 GPM AT 3650 PSI - 420 STAINLESS MANIFOLD

Contact us for pricing

10 GPM @ 3650 PSI | 1450 RPM |  
420 STAINLESS | INLET 1" FNPT,  
OUTLET 1/2" FNPT |



---

**SKU:** KE22A

**Stock:** Out of stock contact us for  
lead time

**Categories:** [General Pump](#)

**Part Number** KE22A

## PRODUCT DESCRIPTION

### FEATURES

- A “New Generation” Pump
- Triplex Plunger Pump, available in 5 flows
- Patent-pending, symmetrical power end design featuring top and bottom mounting holes allowing for easy left to right shaft conversion
- Low-high pressure packing design with integrated cooling system
- High volumetric efficiency suction/delivery valves

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

featuring new spherical design of sealing areas

- Splash lubrication
- SAE-B hydraulic drive bell housing and flexible couplers available

## MATERIALS

- High resistance light alloy die cast aluminum crankcase
  - 420 Stainless steel manifold, nickel treated
    - Taper roller bearings
  - Special antifriction, forged, light alloy connecting rods
- Forged alloy steel crankshaft, hardened, tempered and nitrited
  - Cast iron piston guide, nickel treated
    - Solid ceramic plungers
    - Stainless steel valves
- Pumps are also available with 316 SS packing components.  
These models use prefix "KEN"

## Estimated Delivery 1 to 2 weeks

[KE Specs](#)

[KE Manual](#)

[KE Repair](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	100 lbs
<b>Dimensions</b>	22 × 20 × 14 in
<b>GPM/PSI</b>	<a href="#">10 GPM @ 3650 PSI</a>
<b>Wetted Material</b>	<a href="#">420 SS MANIFOLD</a>

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

## Contact us for pricing

10 GPM @ 3650 PSI | 1450 RPM | 420 STAINLESS | INLET 1" FNPT, OUTLET 1/2" FNPT |