

www.pfcestore.com - 763-425-7890 / 800-328-2350



GENERAL PUMP KE36HA - 26 GPM AT 1450 PSI - 420 STAINLESS MANIFOLD

Contact us for pricing

26 GPM @ 1450 PSI | 1450 RPM | 420 STAINLESS | INLET 1" FNPT, OUTLET 1/2" FNPT |



SKU: KE36HA

Stock: Out of stock contact us for

lead time

Categories: General Pump

Part Number KF36HA

PRODUCT DESCRIPTION

FEATURES

- A "New Generation" Pump
- Triplex Plunger Pump, available in 5 flows
- Patent-pending, symmetrical power end design featuring top and bottom mounting holes allowing for easy left to right shaft conversion
- Low-high pressure packing design with integrated cooling system
 - High volumetric efficiency suction/delivery valves



www.pfcestore.com - 763-425-7890 / 800-328-2350

featuring new spherical design of sealing areas

- Splash lubrication
- SAE-B hydraulic drive bell housing and flexible couplers available

MATERIALS

- High resistance light alloy die cast aluminum crankcase
 - 420 Stainless steel manifold, nickel treated
 - Taper roller bearings
 - Special antifriction, forged, light alloy connecting rods
- Forged alloy steel crankshaft, hardened, tempered and nitrited
 - Cast iron piston guide, nickel treated
 - Solid ceramic plungers
 - Stainless steel valves
 - Pumps are also available with 316 SS packing components.
 These models use prefix "KEN"

Estimated Delivery 1 to 2 weeks

KE Specs

KE Manual

KE Repair

ADDITIONAL INFORMATION

Weight 100 lbs

Dimensions $22 \times 20 \times 14 \text{ in}$

GPM/PSI 26 GPM @ 1450 PSI

Wetted Material 420 SS MANIFOLD