




GENERAL PUMP KE36HA - 26 GPM AT 1450 PSI - 420 STAINLESS MANIFOLD

Contact us for pricing

26 GPM @ 1450 PSI | 1450 RPM |
420 STAINLESS | INLET 1" FNPT,
OUTLET 1/2" FNPT |



SKU: KE36HA

Stock: Out of stock contact us for
lead time

Categories: [General Pump](#)

Part Number KE36HA

PRODUCT DESCRIPTION

FEATURES

- A “New Generation” Pump
- Triplex Plunger Pump, available in 5 flows
- Patent-pending, symmetrical power end design featuring top and bottom mounting holes allowing for easy left to right shaft conversion
- Low-high pressure packing design with integrated cooling system
- High volumetric efficiency suction/delivery valves

www.pfcstore.com - 763-425-7890 / 800-328-2350

featuring new spherical design of sealing areas

- Splash lubrication
- SAE-B hydraulic drive bell housing and flexible couplers available

MATERIALS

- High resistance light alloy die cast aluminum crankcase
 - 420 Stainless steel manifold, nickel treated
 - Taper roller bearings
 - Special antifriction, forged, light alloy connecting rods
- Forged alloy steel crankshaft, hardened, tempered and nitrited
 - Cast iron piston guide, nickel treated
 - Solid ceramic plungers
 - Stainless steel valves
- Pumps are also available with 316 SS packing components.
These models use prefix "KEN"

Estimated Delivery 1 to 2 weeks

[KE Specs](#)

[KE Manual](#)

[KE Repair](#)

ADDITIONAL INFORMATION

Weight	100 lbs
Dimensions	22 × 20 × 14 in
GPM/PSI	26 GPM @ 1450 PSI
Wetted Material	420 SS MANIFOLD

www.pfcstore.com - 763-425-7890 / 800-328-2350

Contact us for pricing

26 GPM @ 1450 PSI | 1450 RPM | 420 STAINLESS | INLET 1" FNPT, OUTLET 1/2" FNPT |