

www.pfcestore.com - 763-425-7890 / 800-328-2350



GENERAL PUMP SM2418R1 - 20 GPM AT 7250 PSI 420 STAINLESS MANIFOLD

Contact us for pricing

20 GPM @ 7250 PSI | 1800 RPM | 420 STAINLESS | INLET 1.5" G, OUTLET 3/4" HP SPECIAL

MAX INLET PRESSURE 100 PSI | MIN INLET PSI 75 PSI

MAX FLUID TEMP 85°F



SKU: SM2418R1

Stock: Out of stock contact us for

lead time

Categories: General Pump

Part Number SM2418R1

PRODUCT DESCRIPTION General Pump SM Series FEATURES



www.pfcestore.com - 763-425-7890 / 800-328-2350

- Triplex Plunger Pump, available in 6 flows
 - Double pressure packings
- Pressure packing integrated cooling system
 - Horizontally fitted in-line valves
 - Splash lubrication
- Gear ratios: 1500 RPM=1.875:1, 1800 RPM=2.238:1,

2200=2.722:1, 2600=3.25:1

Solid shaft only for belt-driven applications

MATERIALS

- · High resistance stainless steel manifold
 - Solid ceramic plungers
 - Forged steel connecting rods
 - Stainless steel valves
 - · Tempered steel alloy crankshaft
 - Cast iron crankcase
 - Double rim roller bearings
 - Proprietary seal technology

Estimated Delivery 1 to 2 weeks

SM Specs

SM Manual

SM Repair

ADDITIONAL INFORMATION

Weight 600 lbs

Dimensions $42 \times 30 \times 20 \text{ in}$

GPM/PSI 20 GPM @ 7250 PSI

Wetted Material 420 SS MANIFOLD



www.pfcestore.com - 763-425-7890 / 800-328-2350