


www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS 01SH06 E-SH PUMP 316SS WITH VITON

316SS | VITON MECH SEAL | 5HP
TEFC PRE EFF, 3500RPM,
3/60/230-460 VOLTS | 1 x 2-6 |
150LB FLANGES | BEP 100 GPM @
109 FTH



SKU: 01SH06A05T3F2
Stock: Out of stock contact us for
lead time
Categories: [Goulds e-SH Pumps](#)
Tags: [GOULDS e-SH PUMPS](#)
Model Number 01SH06A05T3F2

PRODUCT DESCRIPTION

Goulds e-SH Pump 316SS are Superior Materials of Construction: AISI Type 316L stainless steel pump parts for reduced corrosion and improved strength and ductility.

Back Pull-Out Design: Simplifies maintenance when used with spacer type coupling.

Mechanical Seal: Standard John Crane Type 21 mechanical seal.
Suction and Discharge Flanges: Mate with ANSI class 150 flanges.
Close-Coupled Design: Compact design saves space and simplifies maintenance

www.pfcestore.com - 763-425-7890 / 800-328-2350

Enclosed impeller

Estimated delivery is 3 to 4 weeks

Contact us for actual lead time

Product photo could vary from the actual product

[Curve](#)

[Brochure Specs](#)

ADDITIONAL INFORMATION

Weight	130 lbs
Dimensions	36 × 22 × 22 in
Best Efficiency Point	100 GPM @ 109 FTH
Wetted Material	316SS-VITON
Connections	1 X 2
Hertz	60
Horse Power	5
Motor Type	TEFC
Phase	3
RPM	3500
Voltage	230-460