


www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS 03SH08 E-SH PUMP 316SS WITH VITON

316SS | VITON MECH SEAL | 50HP
TEFC PRE EFF, 3500RPM,
3/60/230-460 VOLTS | 3 x 4-8 |
150LB FLANGES | BEP 766 GPM @
177 FTH



SKU: 03SH08E50T3F2

Stock: Out of stock contact us for
lead time

Categories: [Goulds e-SH Pumps](#)

Tags: [GOULDS e-SH PUMPS](#)

Part Number 03SH08E50T3F2

PRODUCT DESCRIPTION

Goulds e-SH Pump 316SS are Superior Materials of Construction: AISI Type 316L stainless steel pump parts for reduced corrosion and improved strength and ductility.

Back Pull-Out Design: Simplifies maintenance when used with spacer type coupling.

Mechanical Seal: Standard John Crane Type 21 mechanical seal.

Suction and Discharge Flanges: Mate with ANSI class 150 flanges.

Close-Coupled Design: Compact design saves space and simplifies maintenance

www.pfcestore.com - 763-425-7890 / 800-328-2350

Enclosed impeller

Estimated delivery is 3 to 4 weeks

Contact us for actual lead time

Product photo could vary from the actual product

[Curve](#)

[Brochure Specs](#)

ADDITIONAL INFORMATION

Weight	750 lbs
Dimensions	42 × 22 × 24 in
Best Efficiency Point	766 GPM @ 177 FTH
Wetted Material	316SS-VITON
Connections	1 X 2
Hertz	60
Horse Power	50
Motor Type	TEFC
Phase	3
RPM	3500
Voltage	230-460