

www.pfcstore.com - 763-425-7890 / 800-328-2350



GOULDS 10SV3GN LOW NPSH CAST IRON 304SS WITH EPR SEAL

BEP 52 GPM @ 145 FTH | Mech
Seal EPR, Max Temp 250°F |
Connections 2" Ansi Flange |
3/60/230-460 Volt, 5HP, 3500 RPM



SKU: 10SV3GG4C66N

Stock: Out of stock contact us for
lead time

Categories: [Goulds Low NPSH
Pumps](#)

Tags: [Goulds Low NPSH Pumps](#)
Model Number 10SV3GG4C66N

PRODUCT DESCRIPTION

GOULDS E-SV LOW NPSH PUMP:

The e-SV fabricated vertical multi-stage pump is an energy saving, non-priming pump coupled to a standard premium-efficient motor. It's built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce lifecycle costs in

www.pfcstore.com - 763-425-7890 / 800-328-2350

a wide range of demanding applications.

Goulds e-SV low NPSH range of pumps features 11 models, and each can be specially configured for a wide range of environments . What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

Estimated delivery is 3 to 4 weeks

[Curves & Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	115 lbs
Dimensions	40 × 22 × 22 in
Best Efficiency Point	<u>52 GPM @ 145 FTH</u>
Connections	<u>2" ANSI FLANGE</u>
Hertz	<u>60</u>
Horse Power	<u>5</u>
Motor Type	<u>TEFC</u>
RPM	<u>3500</u>
Voltage	<u>230-460</u>
Wetted Material	<u>CAST IRON-304SS-EPR</u>