GOULDS 10SV5GN LOW NPSH CAST IRON 304SS WITH VITON SEAL

BEP 52 GPM @ 236 FTH | Mech Seal Viton, Max Temp 250°F | Connections 2" Ansi Flange | 3/60/208-230-460 Volt, 7.5HP, 3500 RPM

SKU: 10SV5GH4F60N
Stock: Out of stock contact us for lead time
Categories: Goulds Low NPSH Pumps
Tags: Goulds Low NPSH Pumps
Model Number 10SV5GH4F60N

PRODUCT DESCRIPTION

GOULDS E-SV LOW NPSH PUMP:

The e-SV fabricated vertical multi-stage pump is an energy saving, non-priming pump coupled to a standard premium-efficient motor. It’s built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce lifecycle costs in

a wide range of demanding applications.

Goulds e-SV low NPSH range of pumps features 11 models, and each can be specially configured for a wide range of environments . What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

Estimated delivery is 3 to 4 weeks

Curves & Specs

Manual

ADDITIONAL INFORMATION

Weight	214 lbs
Dimensions	40 × 22 × 22 in
Best Efficiency Point	52 GPM @ 236 FTH
Connections	2" ANSI FLANGE
Hertz	60
Horse Power	7.5
Motor Type	TEFC
RPM	3500
Voltage	208-230-460
Wetted Material	CAST IRON-304SS-VITON