

www.pfcestore.com - 763-425-7890 / 800-328-2350



## GOULDS 10SV5GN LOW NPSH CAST IRON 304SS WITH VITON SEAL

BEP 52 GPM @ 236 FTH | Mech Seal Viton, Max Temp 250°F | Connections 2" Ansi Flange | 3/60/208-230-460 Volt, 7.5HP, 3500 RPM



**SKU:** 10SV5GH4F60N

**Stock:** Out of stock contact us for lead time

**Categories:** [Goulds Low NPSH Pumps](#)

**Tags:** [Goulds Low NPSH Pumps](#)  
**Model Number** 10SV5GH4F60N

## PRODUCT DESCRIPTION

### GOULDS E-SV LOW NPSH PUMP:

The e-SV fabricated vertical multi-stage pump is an energy saving, non-priming pump coupled to a standard premium-efficient motor. It's built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce lifecycle costs in

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

a wide range of demanding applications.

Goulds e-SV low NPSH range of pumps features 11 models, and each can be specially configured for a wide range of environments . What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

**Estimated delivery is 3 to 4 weeks**

[Curves & Specs](#)

[Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	214 lbs
<b>Dimensions</b>	40 × 22 × 22 in
<b>Best Efficiency Point</b>	<a href="#"><u>52 GPM @ 236 FTH</u></a>
<b>Connections</b>	<a href="#"><u>2" ANSI FLANGE</u></a>
<b>Hertz</b>	<a href="#"><u>60</u></a>
<b>Horse Power</b>	<a href="#"><u>7.5</u></a>
<b>Motor Type</b>	<a href="#"><u>TEFC</u></a>
<b>RPM</b>	<a href="#"><u>3500</u></a>
<b>Voltage</b>	<a href="#"><u>208-230-460</u></a>
<b>Wetted Material</b>	<a href="#"><u>CAST IRON-304SS-VITON</u></a>