PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS 10SV5GN LOW NPSH CAST IRON 304SS WITH VITON SEAL

BEP 52 GPM @ 236 FTH | Mech Seal Viton, Max Temp 250°F | Connections 2" Ansi Flange | 3/60/208-230-460 Volt, 7.5HP, 3500 RPM



SKU: 10SV5GH4F60N

Stock: Out of stock contact us for

lead time

Categories: Goulds e-SV Low

NPSH Pumps

Tags: Goulds Low NPSH Pumps Model Number 10SV5GH4F60N

PRODUCT DESCRIPTION GOULDS E-SV LOW NPSH PUMP:

The e-SV fabricated vertical multi-stage pump is an energy saving, nonpriming pump coupled to a standard premium-efficient motor. It's built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce lifecycle costs in



www.pfcestore.com - 763-425-7890 / 800-328-2350

a wide range of demanding applications.

Goulds e-SV low NPSH range of pumps features 11 models, and each can be specially configured for a wide range of environments . What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

Estimated delivery is 3 to 4 weeks

Curves & Specs

<u>Manual</u>

ADDITIONAL INFORMATION

Weight 214 lbs

Dimensions $40 \times 22 \times 22$ in

Best Efficiency Point 52 GPM @ 236 FTH

Connections 2" ANSI FLANGE

Hertz 60

Horse Power 7.5

Motor Type <u>TEFC</u>

RPM 3500

Voltage <u>208-230-460</u>

Wetted Material CAST IRON-304SS-VITON