

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS 15SH06 PUMP 316SS WITH VITON

316SS | VITON MECH SEAL | 5HP TEFC PRE EFF, 3500RPM, 3/60/230-460 VOLTS | 1-1/2 x 2-1/2-6 | 150LB FLANGES | BEP 144 GPM @ 86 FTH



 SKU: 15SH06D05T3E2
Stock: Out of stock contact us for lead time
Categories: Goulds e-SH Pumps Tags: GOULDS e-SH PUMPS
Part Number 15SH06D05T3E2

PRODUCT DESCRIPTION

Goulds SSH Pump 316SS are Superior Materials of Construction: AISI Type 316L stainless steel pump parts for reduced corrosion and improved strength and ductility.

Back Pull-Out Design: Simplifies maintenance when used with spacer type coupling.

Mechanical Seal: Standard John Crane Type 21 mechanical seal. Suction and Discharge Flanges: Mate with ANSI class 150 flanges. Close-Coupled Design: Compact design saves space and simplifies maintenance

PFC eStore Pumps, Filters & Controls store with B2B



www.pfcestore.com - 763-425-7890 / 800-328-2350

Enclosed impeller

Estimated delivery is 3 to 4 weeks

Contact us for actual lead time

Product photo could vary from the actual product

<u>Curve</u>

Brochure Specs

ADDITIONAL INFORMATION

| Weight | 184 lbs |
|------------------------------|-------------------------|
| Dimensions | 36 × 22 × 22 in |
| Best Efficiency Point | <u>144 GPM @ 86 FTH</u> |
| Wetted Material | 316SS-VITON |
| Connections | <u>1.5 X 2.5</u> |
| Hertz | <u>60</u> |
| Horse Power | <u>5</u> |
| Motor Type | <u>TEFC</u> |
| Phase | <u>3</u> |
| RPM | <u>3500</u> |
| Voltage | <u>230-460</u> |