


www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS 15SH10 PUMP 316SS WITH VITON

316SS | VITON MECH SEAL | 20HP
TEFC, 3500RPM, 3/60/208-230-460
VOLTS | 1.5 x 2.5-10 | 150LB
FLANGES | BEP 230 GPM @ 190
FTH



SKU: 15SH10E20T3E2

Stock: Out of stock contact us for
lead time

Categories: [Goulds e-SH Pumps](#)

Tags: [GOULDS e-SH PUMPS](#)

Part Number 15SH10E20T3E2

PRODUCT DESCRIPTION

Goulds SSH Pump 316SS are Superior Materials of Construction: AISI Type 316L stainless steel pump parts for reduced corrosion and improved strength and ductility.

Back Pull-Out Design: Simplifies maintenance when used with spacer type coupling.

Mechanical Seal: Standard John Crane Type 21 mechanical seal.

Suction and Discharge Flanges: Mate with ANSI class 150 flanges.

Close-Coupled Design: Compact design saves space and simplifies maintenance

www.pfcstore.com - 763-425-7890 / 800-328-2350

Enclosed impeller

Estimated delivery is 3 to 4 weeks

Contact us for actual lead time

Product photo could vary from the actual product

[Curve](#)

[Brochure Specs](#)

ADDITIONAL INFORMATION

Weight	410 lbs
Dimensions	42 × 22 × 22 in
Best Efficiency Point	230 GPM @ 190 FTH
Connections	1.5 X 2.5
Hertz	60
Horse Power	20
Motor Type	TEFC
Phase	3
RPM	3500
Voltage	208-230-460
Wetted Material	316SS-VITON