

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS 15SH10 PUMP 316SS WITH VITON

316SS | VITON MECH SEAL | 25HP ODPPE, 3500RPM, 3/60/208-230-460 VOLTS | 1.5 x 2.5-10 | 150LB FLANGES | BEP 204 GPM @ 264 FTH



 SKU: 15SH10C25T3E2
Stock: Out of stock contact us for lead time
Categories: Goulds e-SH Pumps Tags: GOULDS e-SH PUMPS
Part Number 15SH10C25T3E2

PRODUCT DESCRIPTION

Goulds e-SH Pump 316SS are Superior Materials of Construction: AISI Type 316L stainless steel pump parts for reduced corrosion and improved strength and ductility.

Back Pull-Out Design: Simplifies maintenance when used with spacer type coupling.

Mechanical Seal: Standard John Crane Type 21 mechanical seal. Suction and Discharge Flanges: Mate with ANSI class 150 flanges. Close-Coupled Design: Compact design saves space and simplifies maintenance

Page: 1

PFC eStore Pumps, Filters & Controls store with B2B August 24, 2025



www.pfcestore.com - 763-425-7890 / 800-328-2350

Enclosed impeller

Estimated delivery is 3 to 4 weeks

Contact us for actual lead time

Product photo could vary from the actual product

<u>Curve</u>

Brochure Specs

ADDITIONAL INFORMATION

Weight	420 lbs
Dimensions	42 × 22 × 22 in
Best Efficiency Point	<u>204 GPM @ 264 FTH</u>
Connections	<u>1.5 X 2.5</u>
Hertz	<u>60</u>
Horse Power	<u>25</u>
Motor Type	<u>TEFC</u>
Phase	<u>3</u>
RPM	<u>3500</u>
Voltage	<u>208-230-460</u>
Wetted Material	<u>316SS-VITON</u>