

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS 25SH06 E-SH PUMP 316SS WITH VITON

316SS | VITON MECH SEAL | 20HP TEFC PRE EFF, 3500RPM, 3/60/230-460 VOLTS | 2.5 x 3-6 | 150LB FLANGES | BEP 367 GPM @ 136 FTH



SKU: 25SH06C20T3E2

Stock: Out of stock contact us for

lead time

Categories: Goulds e-SH Pumps

Tags: GOULDS e-SH PUMPS
Part Number 25SH06C20T3E2

PRODUCT DESCRIPTION

Goulds e-SH Pump 316SS are Superior Materials of Construction: AISI Type 316L stainless steel pump parts for reduced corrosion and improved strength and ductility.

Back Pull-Out Design: Simplifies maintenance when used with spacer type coupling.

Mechanical Seal: Standard John Crane Type 21 mechanical seal. Suction and Discharge Flanges: Mate with ANSI class 150 flanges. Close-Coupled Design: Compact design saves space and simplifies maintenance



www.pfcestore.com - 763-425-7890 / 800-328-2350

Enclosed impeller

Estimated delivery is 3 to 4 weeks

Contact us for actual lead time

Product photo could vary from the actual product

Curve

Brochure Specs

ADDITIONAL INFORMATION

Weight 350 lbs

Dimensions $36 \times 22 \times 22$ in

Best Efficiency Point 367 GPM @ 136 FTH

Connections 2.5 X 3

Hertz <u>60</u>

Horse Power <u>20</u>

Motor Type <u>TEFC</u>

Phase <u>3</u>

RPM 3500

Voltage <u>230-460</u>

Wetted Material 316SS-VITON