


www.pfcstore.com - 763-425-7890 / 800-328-2350



## GOULDS 25SH08 E-SH PUMP 316SS WITH VITON

316SS | VITON MECH SEAL | 30HP  
TEFC PRE EFF, 3500RPM,  
3/60/230-460 VOLTS | 2.5 x 3-8 |  
150LB FLANGES | BEP 384 GPM @  
190 FTH



**SKU:** 25SH08G30T3F2

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Goulds e-SH Pumps](#)

**Tags:** [GOULDS e-SH PUMPS](#)

**Part Number** 25SH08G30T3F2

## PRODUCT DESCRIPTION

Goulds e-SH Pump 316SS are Superior Materials of Construction: AISI Type 316L stainless steel pump parts for reduced corrosion and improved strength and ductility.

Back Pull-Out Design: Simplifies maintenance when used with spacer type coupling.

Mechanical Seal: Standard John Crane Type 21 mechanical seal.

Suction and Discharge Flanges: Mate with ANSI class 150 flanges.

Close-Coupled Design: Compact design saves space and simplifies maintenance

www.pfcstore.com - 763-425-7890 / 800-328-2350

Enclosed impeller

Estimated delivery is 3 to 4 weeks

Contact us for actual lead time

Product photo could vary from the actual product

[Curve](#)

[Brochure Specs](#)

ADDITIONAL INFORMATION

Weight	551 lbs
Dimensions	36 × 22 × 22 in
Best Efficiency Point	<a href="#">384 GPM @ 190 FTH</a>
Connections	<a href="#">2.5 X 3</a>
Hertz	<a href="#">60</a>
Horse Power	<a href="#">30</a>
Motor Type	<a href="#">TEFC</a>
Phase	<a href="#">3</a>
RPM	<a href="#">3500</a>
Voltage	<a href="#">230-460</a>
Wetted Material	<a href="#">316SS-VITON</a>