

www.pfcstore.com - 763-425-7890 / 800-328-2350



GOULDS 3656M PUMP IN ALL IRON WITH BUNA SEAL 25 HP 16AI

CAST IRON / BUNA MECH SEAL |
25 HP TEFC, 3500RPM,
3/60/230-460 VOLTS | 3 X 4-8 | BEP
400 GPM @ 150 FTH



SKU: 16AI1P9E0

Stock: Out of stock contact us for
lead time

Categories: [Goulds 3656 Pumps](#)

Part Number 16AI1P9E0

PRODUCT DESCRIPTION

Goulds 3656M Pump

- Back pull-out to reduce maintenance down time.
- Standard John Crane Type 21 mechanical seal for both reliability and availability. Carbon/ceramic/ BUNA standard, with other faces and elastomers available.
- Available in all iron or bronze fitted construction for application versatility.
- Replaceable wearing components include stainless steel shaft sleeve

www.pfcstore.com - 763-425-7890 / 800-328-2350

and casing and hub wear rings to maintain peak efficiency.

- Enclosed impeller design, dynamic balancing and renewable wear rings reduce losses affecting performance and pump life.
- 125 lb. ANSI flange suction/discharge connections and casing rotation for piping connection versatility.
- NPT threaded connections are supplied on 1 1/2 x 2 - 10 and 2 1/2 x 3 - 8 models.

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

[Curve](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	860 lbs
Dimensions	38 × 16 × 17 in
Best Efficiency Point	400 GPM @ 150 FTH
Connections	3 X 4
Hertz	60
Horse Power	25
Motor Type	TEFC
Phase	3
RPM	3500
Voltage	230-460
Wetted Material	CAST IRON-BUNA

www.pfcestore.com - 763-425-7890 / 800-328-2350

CAST IRON / BUNA MECH SEAL | 25 HP TEFC, 3500RPM, 3/60/230-460 VOLTS |
3 X 4-8 | BEP 400 GPM @ 150 FTH