

www.pfcstore.com - 763-425-7890 / 800-328-2350



GOULDS 3656M PUMP IN CAST IRON BRONZE FITTED WITH BUNA SEAL 10 HP 16BF

CAST IRON / BRONZE / BUNA MECH
SEAL | 10 HP TEFC, 3500RPM,
3/60/230-460 VOLTS | 3 X 4-8 | BEP
300 GPM @ 90 FTH



SKU: 16BF1L9H0

Stock: Out of stock contact us for
lead time

Categories: [Goulds 3656 Pumps](#)

Part Number 16BF1L9H0

PRODUCT DESCRIPTION

Goulds 3656M Pump

- Back pull-out to reduce maintenance down time.
- Standard John Crane Type 21 mechanical seal for both reliability and availability. Carbon/ceramic/ BUNA standard, with other faces and elastomers available.
- Available in all iron or bronze fitted construction for application versatility.

www.pfcestore.com - 763-425-7890 / 800-328-2350

- Replaceable wearing components include stainless steel shaft sleeve and casing and hub wear rings to maintain peak efficiency.
- Enclosed impeller design, dynamic balancing and renewable wear rings reduce losses affecting performance and pump life.
- 125 lb. ANSI flange suction/discharge connections and casing rotation for piping connection versatility.
- NPT threaded connections are supplied on 1 1/2 x 2 - 10 and 2 1/2 x 3 - 8 models.

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

[Curve](#)

[Manual](#)

ADDITIONAL INFORMATION

| | |
|------------------------------|-------------------------|
| Weight | 370 lbs |
| Dimensions | 38 × 16 × 17 in |
| Best Efficiency Point | <u>300 GPM @ 90 FTH</u> |
| Connections | <u>3 X 4</u> |
| Hertz | <u>60</u> |
| Horse Power | <u>10</u> |
| Motor Type | <u>TEFC</u> |
| Phase | <u>3</u> |
| RPM | <u>3500</u> |
| Voltage | <u>230-460</u> |
| Wetted Material | <u>IRON/BRONZE-BUNA</u> |

www.pfcestore.com - 763-425-7890 / 800-328-2350

CAST IRON / BRONZE / BUNA MECH SEAL | 10 HP TEFC, 3500RPM,
3/60/230-460 VOLTS | 3 X 4-8 | BEP 300 GPM @ 90 FTH