

www.pfcstore.com - 763-425-7890 / 800-328-2350



## GOULDS 3656M PUMP IN CAST IRON BRONZE FITTED WITH BUNA SEAL 20 HP 16BF

CAST IRON / BRONZE / BUNA MECH  
SEAL | 20 HP TEFC, 3500RPM,  
3/60/230-460 VOLTS | 3 X 4-8 | BEP  
350 GPM @ 120 FTH



---

**SKU:** 16BF1N9F0

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Goulds 3656 Pumps](#)

**Part Number** 16BF1N9F0

## PRODUCT DESCRIPTION

### Goulds 3656M Pump

- Back pull-out to reduce maintenance down time.
- Standard John Crane Type 21 mechanical seal for both reliability and availability. Carbon/ceramic/ BUNA standard, with other faces and elastomers available.
- Available in all iron or bronze fitted construction for application versatility.

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

- Replaceable wearing components include stainless steel shaft sleeve and casing and hub wear rings to maintain peak efficiency.
- Enclosed impeller design, dynamic balancing and renewable wear rings reduce losses affecting performance and pump life.
- 125 lb. ANSI flange suction/discharge connections and casing rotation for piping connection versatility.
- NPT threaded connections are supplied on 1 1/2 x 2 - 10 and 2 1/2 x 3 - 8 models.

Product photo could vary from the actual product

**Estimated delivery is 3 to 4 weeks**

[Curve](#)

[Manual](#)

## ADDITIONAL INFORMATION

<b>Weight</b>	655 lbs
<b>Dimensions</b>	38 x 16 x 17 in
<b>Best Efficiency Point</b>	<a href="#">350 GPM @ 120 FTH</a>
<b>Connections</b>	<a href="#">3 X 4</a>
<b>Hertz</b>	<a href="#">60</a>
<b>Horse Power</b>	<a href="#">20</a>
<b>Motor Type</b>	<a href="#">TEFC</a>
<b>Phase</b>	<a href="#">3</a>
<b>RPM</b>	<a href="#">3500</a>
<b>Voltage</b>	<a href="#">230-460</a>
<b>Wetted Material</b>	<a href="#">IRON/BRONZE-BUNA</a>

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350