

www.pfcstore.com - 763-425-7890 / 800-328-2350



GOULDS 3656M PUMP IN CAST IRON BRONZE FITTED WITH BUNA SEAL 25 HP 16BF

CAST IRON / BRONZE / BUNA MECH
SEAL | 25 HP TEFC, 3500RPM,
3/60/230-460 VOLTS | 3 X 4-8 | BEP
400 GPM @ 145 FTH



SKU: 16BF1P9E0

Stock: Out of stock contact us for
lead time

Categories: [Goulds 3656 Pumps](#)

Part Number 16BF1P9E0

PRODUCT DESCRIPTION

Goulds 3656M Pump

- Back pull-out to reduce maintenance down time.
- Standard John Crane Type 21 mechanical seal for both reliability and availability. Carbon/ceramic/ BUNA standard, with other faces and elastomers available.
- Available in all iron or bronze fitted construction for application versatility.

www.pfcestore.com - 763-425-7890 / 800-328-2350

- Replaceable wearing components include stainless steel shaft sleeve and casing and hub wear rings to maintain peak efficiency.
- Enclosed impeller design, dynamic balancing and renewable wear rings reduce losses affecting performance and pump life.
- 125 lb. ANSI flange suction/discharge connections and casing rotation for piping connection versatility.
- NPT threaded connections are supplied on 1 1/2 x 2 – 10 and 2 1/2 x 3 – 8 models.

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

[Curve](#)

[Manual](#)

ADDITIONAL INFORMATION

| | |
|-----------------------|-----------------------------------|
| Weight | 670 lbs |
| Dimensions | 38 × 16 × 17 in |
| Best Efficiency Point | 400 GPM @ 145 FTH |
| Connections | 3 X 4 |
| Hertz | 60 |
| Horse Power | 25 |
| Motor Type | TEFC |
| Phase | 3 |
| RPM | 3500 |
| Voltage | 230-460 |
| Wetted Material | IRON/BRONZE-BUNA |

www.pfcestore.com - 763-425-7890 / 800-328-2350