

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS 3656M PUMP IN CAST IRON BRONZE FITTED WITH BUNA SEAL 25 HP 16BF

CAST IRON / BRONZE / BUNA MECH SEAL | 25 HP TEFC, 3500RPM, 3/60/230-460 VOLTS | 3 X 4-8 | BEP 400 GPM @ 145 FTH



SKU: 16BF1P9E0 Stock: Out of stock contact us for lead time Categories: <u>Goulds 3656 Pumps</u>

Part Number 16BF1P9E0

PRODUCT DESCRIPTION

Goulds 3656M Pump

• Back pull-out to reduce maintenance down time.

• Standard John Crane Type 21 mechanical seal for both reliability and availability. Carbon/ceramic/ BUNA standard, with other faces and elastomers available.

• Available in all iron or bronze fitted construction for application versatility.

PFC eStore Pumps, Filters & Controls store with B2B solution



www.pfcestore.com - 763-425-7890 / 800-328-2350

- Replaceable wearing components include stainless steel shaft sleeve and casing and hub wear rings to maintain peak efficiency.
- Enclosed impeller design, dynamic balancing and renewable wear rings reduce losses affecting performance and pump life.
- 125 lb. ANSI flange suction/discharge connections and casing rotation for piping connection versatility.
- NPT threaded connections are supplied on 1 1/2 x 2 10 and 2 1/2 x 3 8 models.

Product photo could vary from the actual product

Estimated delivery is 3 to 4 weeks

<u>Curve</u>

<u>Manual</u>

ADDITIONAL INFORMATION

| Weight | 670 lbs |
|------------------------------|--------------------------|
| Dimensions | 38 × 16 × 17 in |
| Best Efficiency Point | <u>400 GPM @ 145 FTH</u> |
| Connections | <u>3 X 4</u> |
| Hertz | <u>60</u> |
| Horse Power | <u>25</u> |
| Motor Type | <u>TEFC</u> |
| Phase | <u>3</u> |
| RPM | <u>3500</u> |
| Voltage | <u>230-460</u> |
| Wetted Material | IRON/BRONZE-BUNA |

PFC eStore



www.pfcestore.com - 763-425-7890 / 800-328-2350