



GOULDS 46SV50GN LOW NPSH CAST IRON 304SS WITH VITON SEAL

BEP 230 GPM @ 500 FTH | Mech
Seal Viton, Max Temp 250°F |
Connections 3" Ansi Flange |
3/60/230-460 Volt, 40HP, 3500
RPM



SKU: 46SV50GP4C60N

Stock: Out of stock contact us for
lead time

Categories: [Goulds e-SV Low
NPSH Pumps](#)

Model Number 46SV50GP4C60N

PRODUCT DESCRIPTION

GOULDS E-SV LOW NPSH PUMP:

The e-SV fabricated vertical multi-stage pump is an energy saving, non-priming pump coupled to a standard premium-efficient motor. It's built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce lifecycle costs in

www.pfcstore.com - 763-425-7890 / 800-328-2350

a wide range of demanding applications.

Goulds e-SV low NPSH range of pumps features 11 models, and each can be specially configured for a wide range of environments . What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

Estimated delivery is 3 to 4 weeks

[Curves & Specs](#)

[Manual](#)

ADDITIONAL INFORMATION

Weight	855 lbs
Dimensions	70 × 22 × 22 in
Best Efficiency Point	230 GPM @ 500 FTH
Connections	3" ANSI FLANGE
Hertz	60
Horse Power	40
Motor Type	TEFC
RPM	3500
Voltage	230-460
Wetted Material	CAST IRON-304SS-VITON

www.pfcstore.com - 763-425-7890 / 800-328-2350

BEP 230 GPM @ 500 FTH | Mech Seal Viton, Max Temp 250°F | Connections 3" Ansi Flange | 3/60/230-460 Volt, 40HP, 3500 RPM