PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS 46SV50GN LOW NPSH CAST IRON 304SS WITH VITON SEAL

BEP 230 GPM @ 500 FTH | Mech Seal Viton, Max Temp 250°F | Connections 3" Ansi Flange | 3/60/230-460 Volt, 40HP, 3500 RPM



SKU: 46SV50GP4C60N **Stock:** Out of stock contact us for

lead time

Categories: Goulds Low NPSH

<u>Pumps</u>

Tags: Goulds Low NPSH Pumps
Model Number 46SV50GP4C60N

PRODUCT DESCRIPTION GOULDS E-SV LOW NPSH PUMP:

The e-SV fabricated vertical multi-stage pump is an energy saving, nonpriming pump coupled to a standard premium-efficient motor. It's built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce lifecycle costs in



www.pfcestore.com - 763-425-7890 / 800-328-2350

a wide range of demanding applications.

Goulds e-SV low NPSH range of pumps features 11 models, and each can be specially configured for a wide range of environments . What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

Estimated delivery is 3 to 4 weeks

Curves & Specs

<u>Manual</u>

ADDITIONAL INFORMATION

Weight 855 lbs

Dimensions $70 \times 22 \times 22$ in

Best Efficiency Point 230 GPM @ 500 FTH

Connections 3" ANSI FLANGE

Hertz <u>60</u>

Horse Power 40

Motor Type <u>TEFC</u>

RPM 3500

Voltage <u>230-460</u>

Wetted Material CAST IRON-304SS-VITON