



## GOULDS 46SV70GN LOW NPSH CAST IRON 304SS WITH VITON SEAL

BEP 230 GPM @ 700 FTH | Mech  
Seal Viton, Max Temp 250°F |  
Connections 3" Ansi Flange |  
3/60/230-460 Volt, 60HP, 3500  
RPM



---

**SKU:** 46SV70GS4C60N

**Stock:** Out of stock contact us for  
lead time

**Categories:** [Goulds e-SV Low  
NPSH Pumps](#)

**Model Number** 46SV70GS4C60N

## PRODUCT DESCRIPTION

### GOULDS E-SV LOW NPSH PUMP:

The e-SV fabricated vertical multi-stage pump is an energy saving, non-priming pump coupled to a standard premium-efficient motor. It's built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce lifecycle costs in

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

a wide range of demanding applications.

Goulds e-SV low NPSH range of pumps features 11 models, and each can be specially configured for a wide range of environments . What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

## Estimated delivery is 3 to 4 weeks

[Curves & Specs](#)

[Manual](#)

### ADDITIONAL INFORMATION

<b>Weight</b>	1395 lbs
<b>Dimensions</b>	80 × 22 × 22 in
<b>Best Efficiency Point</b>	<a href="#">230 GPM @ 700 FTH</a>
<b>Connections</b>	<a href="#">3" ANSI FLANGE</a>
<b>Hertz</b>	<a href="#">60</a>
<b>Horse Power</b>	<a href="#">60</a>
<b>Motor Type</b>	<a href="#">TEFC</a>
<b>RPM</b>	<a href="#">3500</a>
<b>Voltage</b>	<a href="#">230-460</a>
<b>Wetted Material</b>	<a href="#">CAST IRON-304SS-VITON</a>

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

BEP 230 GPM @ 700 FTH | Mech Seal Viton, Max Temp 250°F | Connections 3" Ansi Flange | 3/60/230-460 Volt, 60HP, 3500 RPM