PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS AQUAFORCE DUPLEX BOOSTER SYSTEM, 460V, 3 PHASE, HVX2D8R-125SVX10CGLA XX0-G

Two Pumps BEP - 1130 GPM @ 85 FTH. Material - Cast Iron/304SS. Mechanical Seal Car/Silcar Viton. Connections 8"

Picture shows a Triplex Booster with panel on right side



SKU:

HVX2D8R-125SVX10CGLAXX0-G **Stock:** Out of stock contact us for lead time

Categories: Goulds Booster Skids

PRODUCT DESCRIPTION

The AQUAFORCE™ e-HVX & e-HVXR Packaged Booster Systems are advanced variable speed pumping stations, featuring two or three e-SVX Series multistage vertical Smart Pumps. Each pump is equipped with a



www.pfcestore.com - 763-425-7890 / 800-328-2350

hydrovar® X Smart Motor, enabling variable speed operation. These systems enhance user comfort by reducing noise emissions and minimizing "water hammer" through gradual pump staging and shutdown. All pumps are mounted on a single base, with

individual shut-off and check valves. The system is interconnected by suction and delivery manifolds, and the control panel is securely attached to the same base with a bracket.

Estimated delivery is 3 to 4 weeks - Please contact us for current delivery

Specs & Curve

Technical Brochure

<u>Manual</u>

ADDITIONAL INFORMATION

Weight 1538 lbs

Dimensions $70 \times 84 \times 60 \text{ in}$

Best Efficiency Point 1130 GPM @ 85 FTH

Input Volts 380-460

Wetted Material CAST IRON-304SS-VITON