

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS AQUAFORCE TRIPLEX BOOSTER SYSTEM, 460V, 3 PHASE, HVXR3D4R-15SVX7RKAXX 0-G

Three Pumps BEP - 280 GPM @ 390 FTH. Material - Cast Iron/304SS. Mechanical Seal Car/Silcar Viton. Connections 3"

Picture shows a Triplex Booster with panel on right side



SKU: HVXR3D4R-15SVX7RKAXX0-

G

Stock: Out of stock contact us for

lead time

Categories: Goulds Booster Skids

PRODUCT DESCRIPTION

The AQUAFORCE™ e-HVX & e-HVXR Packaged Booster Systems are advanced variable speed pumping stations, featuring two or three e-SVX Series multistage vertical Smart Pumps. Each pump is equipped with a



www.pfcestore.com - 763-425-7890 / 800-328-2350

hydrovar® X Smart Motor, enabling variable speed operation. These systems enhance user comfort by reducing noise emissions and minimizing "water hammer" through gradual pump staging and shutdown. All pumps are mounted on a single base, with

individual shut-off and check valves. The system is interconnected by suction and delivery manifolds, and the control panel is securely attached to the same base with a bracket.

Estimated delivery is 3 to 4 weeks - Please contact us for current delivery

Specs & Curve

Technical Brochure

Manual

ADDITIONAL INFORMATION

Weight 1253 lbs

Dimensions $65 \times 44 \times 60 \text{ in}$

Best Efficiency Point 280 GPM @ 390 FTH

Input Volts <u>380-460</u>

Wetted Material <u>CAST IRON-304SS-VITON</u>