



## GOULDS CENTRIFUGAL PUMP 125SV50G IN CAST IRON & VITON

Wetted Parts: Cast Iron, Viton Seal  
| 3 Phase | 75 hp | 3500 rpm | 5"  
Flanges | BEP 520 GPM @ 450 FTH



**SKU:** 125SV50CGT4C60

**Stock:** Out of stock contact us for lead time

**Categories:** [Goulds Cast Iron/304SS Pumps](#)

**Tags:** [GOULDS ESVN PUMPS](#)

**Model Number** 125SV50CGT4C60

**Part Number** eSV Series

## PRODUCT DESCRIPTION

### E-SV PUMP:

Goulds e-SV pump fabricated vertical multi-stage pump is an energy saving, non-priming pump coupled to a standard premium-efficient motor.

It's built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce

[www.pfcestore.com](http://www.pfcestore.com) - 763-425-7890 / 800-328-2350

lifecycle costs in a wide range of demanding applications.

The e-SV range of pumps features 11 models, and each can be specially configured for a wide range of environments. What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

### **Estimated delivery is 3 to 4 weeks**

Contact us for actual delivery

Product photo could vary from the actual product

[Curve](#)

[Technical Brochure](#)

### **ADDITIONAL INFORMATION**

|                              |  |
|------------------------------|--|
| <b>Weight</b>                | 1386 lbs                                 |
| <b>Dimensions</b>            | 60 × 28 × 28 in                          |
| <b>Best Efficiency Point</b> | <a href="#"><u>520 GPM @ 450 FTH</u></a> |
| <b>Connections</b>           | <a href="#"><u>5" ANSI FLANGE</u></a>    |
| <b>Hertz</b>                 | <a href="#"><u>60</u></a>                |
| <b>Horse Power</b>           | <a href="#"><u>75</u></a>                |
| <b>Motor Type</b>            | <a href="#"><u>TEFC</u></a>              |
| <b>Phase</b>                 | <a href="#"><u>3</u></a>                 |
| <b>RPM</b>                   | <a href="#"><u>3500</u></a>              |
| <b>Voltage</b>               | <a href="#"><u>208-230-460</u></a>       |

[www.pfcstore.com](http://www.pfcstore.com) - 763-425-7890 / 800-328-2350

**Wetted Material**

[316SS-VITON](#)