PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

GOULDS CENTRIFUGAL PUMP 5SV22N IN 316SS & VITON

Wetted Parts: 316SS, Viton Seal | 3 Phase | 7.5 hp | 3500 rpm | 1.25" Flanges | BEP 30 GPM @ 595 FTH

SKU: 5SV22NH4F60
Stock: Out of stock contact us for lead time
Categories: Goulds 316SS Pumps
Tags: GOULDS ESVN PUMPS
Model Number 5SV22NH4F60
Part Number eSV Series

PRODUCT DESCRIPTION

E-SV PUMP:

Goulds e-SV pump fabricated vertical multi-stage pump is an energy saving, non-priming pump coupled to a standard premium-efficient motor. It’s built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce

lifecycle costs in a wide range of demanding applications.

The e-SV range of pumps features 11 models, and each can be specially configured for a wide range of environments. What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

Estimated delivery is 3 to 4 weeks

Contact us for actual delivery

Product photo could vary from the actual product

Curve

Technical Brochure

ADDITIONAL INFORMATION

Weight	220 lbs
Dimensions	60 × 20 × 22 in
Best Efficiency Point	30 GPM @ 595 FTH
Connections	1.25" Flange
Hertz	60
Horse Power	7.5
Motor Type	TEFC
Phase	3
RPM	3500
Voltage	208-230-460

PFC eSTORE
Clear Solutions Technology Company

www.pfcestore.com - 763-425-7890 / 800-328-2350

Wetted Material	316SS-VITON