



GOULDS CENTRIFUGAL PUMP 5SV24G IN CAST IRON, 304SS & VITON

Wetted Parts: Cast Iron, 304SS, Viton Seal | 7.5HP | 3 Phase | TEFC | 3500 rpm | 1.25" Flanges| BEP 30 GPM @637 FTH



SKU: 5SV24GH4F60

Stock: Out of stock contact us for lead time

Categories: [Goulds e-SV Cast Iron/304SS Pumps](#)

Model Number 5SV24GH4F60
Part Number eSV Series

PRODUCT DESCRIPTION

E-SV PUMP:

Goulds e-SV pump fabricated vertical multi-stage pump is an energy saving, non-priming pump coupled to a standard premium-efficient motor. It's built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce

www.pfcstore.com - 763-425-7890 / 800-328-2350

lifecycle costs in a wide range of demanding applications.

The e-SV range of pumps features 11 models, and each can be specially configured for a wide range of environments. What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

Estimated delivery is 3 to 4 weeks

Contact us for actual delivery

Product photo could vary from the actual product

[Curve](#)

[Technical Brochure](#)

ADDITIONAL INFORMATION

Weight	315 lbs
Dimensions	36 × 20 × 20 in
Best Efficiency Point	30 GPM @ 637 TDH
Connections	1.25" Flange
Hertz	60
Horse Power	7.5
Motor Type	TEFC
Phase	3
RPM	3500
Voltage	208-230-460

www.pfcstore.com - 763-425-7890 / 800-328-2350

Wetted Material

CAST IRON-304SS-VITON

Wetted Parts: Cast Iron, 304SS, Viton Seal | 7.5HP | 3 Phase | TEFC | 3500 rpm | 1.25" Flanges| BEP 30 GPM @637 FTH