PFC eSTORE

www.pfcestore.com - 763-425-7890 / 800-328-2350



GOULDS CENTRIFUGAL PUMP 5SV5G IN CAST IRON, 304SS & VITON

Wetted Parts: Cast Iron, 304SS, Viton Seal | 3 Phase TEFC | 1.5 hp | 3500 rpm | 1.25" Flanges| BEP 32 GPM @110 FTH



SKU: 5SV5GD4F60 **Stock:** Out of stock contact us for

lead time

Categories: Goulds Cast Iron/304SS Pumps

Tags: GOULDS ESVG PUMPS
Model Number 5SV5GD4F60
Part Number eSV Series

PRODUCT DESCRIPTION E-SV PUMP:

Goulds e-SV pump fabricated vertical multi-stage pump is an energy saving, non-priming pump coupled to a standard premium-efficient motor. It's built to withstand a variety of, mechanically aggressive and high temperature liquids, and is designed to extend uptime and help reduce



www.pfcestore.com - 763-425-7890 / 800-328-2350

lifecycle costs in a wide range of demanding applications.

The e-SV range of pumps features 11 models, and each can be specially configured for a wide range of environments. What's more, when an e-SV is paired with a Hydrovar® or Aquavar® IPC variable speed drive, it provides energy saving increases up to 70% vs. fixed speed, while reducing installation time.

Estimated delivery is 3 to 4 weeks

Contact us for actual delivery

Product photo could vary from the actual product

Curve

Technical Brochure

ADDITIONAL INFORMATION

Weight 92 lbs

Dimensions $36 \times 20 \times 20 \text{ in}$

Best Efficiency Point 30 GPM @ 110 FTH

Connections 1.25" Flange

Hertz <u>60</u>

Horse Power 1.5

Motor Type <u>TEFC</u>

Phase 3

RPM 3500

Voltage <u>208-230-460</u>



www.pfcestore.com - 763-425-7890 / 800-328-2350

Wetted Material CAST IRON-304SS-VITON